



APPENDIX A

1. ((Once] Twice Amended) A CDMA cellular telecommunications messaging system, comprising:

a message generator in a mobile switching center for generating an IS-634 message signal, said message signal for transmission to a base station for triggering said base station to transmit a subsequent message signal to a mobile station; and

a message receiver in said base station for receiving said message signal;

wherein said message signal is generated upon detection by said mobile switching center of a condition whereby a mobile subscriber attempts to originate a call while another party is attempting to call the same mobile subscriber.

6. ((Once] Twice Amended) A CDMA cellular communication system, comprising:

a mobile station;

a base station in communication with said mobile station via an Air-Interface, said base station defining a first cellular coverage area;

a mobile switching center in communication with said base station via an IS-634 A-Interface;

a message generator at said mobile switching center for generating a message signal for transmission to said first base station on said A-Interface; and

a message receiver at said base station for receiving said message signal, wherein upon receipt of said message signal, said first base station transmits a subsequent message signal to said mobile station on said Air-Interface;

wherein said message generator generates said message signal when said mobile switching center detects a condition whereby a mobile subscriber attempts to originate a call while another party is attempting to call the same mobile subscriber .

11. ([Once] Twice Amended) In a CDMA wireless communication system, a method for messaging between a mobile switching center and a base station, comprising the steps of:

detecting the occurrence of a condition whereby a mobile subscriber attempts to originate a call while another party is attempting to call the same mobile subscriber;

generating a message signal in said mobile switching center based on a positive result of said step of detecting; and

transmitting said message signal to said base station on an IS-634 A-Interface, wherein upon receipt of said message signal, said base station transmits a subsequent message signal to a mobile station on an Air-Interface.